

AK-S560

AKUVOX



Features

- Akuvox
- Video intercom
- Status LED and function keys
- Built-in microphone and speaker
- Two-way audio with Crystal Clear technology
- Automatic voice detection
- TCP/IP
- 1 PoE port IEEE802.3af
- Surface mounting
- Easy-to-integrate SIP standard
- Complete configuration via Web browser
- Push notifications and calls between devices through SmartPlus APP
- 4 users included for each dwelling Single Family (free) and Community (under subscription)
- Firmware upgrades via cloud with installer control
- Connection between boards and monitors via cloud in different networks
- Remote configuration access for installation

Specifications

Brand	Akuvox
Model	S560
Operating system	Linux
Audio	Two-way audio with noise-reduced microphone and speaker with Crystal Clear Audio technology
Audio Format	SIP v1 (RFC2543), SIP v2 (RFC3261), G.711a, G.711?, G.729, G.722 DTMF (RFC2833), SIP Info
Remote access	SmartPlus cell phone application or configuration via WEB browser Remote access by Cloud: Included
Mode of operation	Local network and/or via cloud in different networks
Firmware updates	Remote with cloud via installer account or via web browser locally
Network interface	Ethernet 10/100 BaseT
Power	DC 12 V / 600 mA máx. Standard PoE (IEEE802.3af)
Temp. operation	-10 °C ~ +45 °C
Dimensions	216 (W) x 63 (H) x 53 (D) mm
Weight	400 g