AK-S565W

AKUVOX



Features

- Akuvox
- Linux IPS display for 10" video door entry system
- Easy UI user interface
- Integrated dual microphone and speaker
- Two-way audio with Crystal Clear technology
- 1 buzzer input and 8 alarm input
- 1 relay output
- Image capture and recording
- Multiple screen extensions
- TCP/IP and WiFi

- 1 PoE port IEEE802.3af
- Surface mounting with additional accessory
- Easy-to-integrate SIP standard
- Complete configuration via Web browser
- Push notifications and calls between devices through SmartPlus APP
- 4 free users included per house
- Call and user directory
- Firmware upgrades via cloud with installer control
- Camera viewing via RTSP and ONVIF
- Connection between boards and monitors via cloud in different networks

Specifications

Brand	Akuvox
Dialiu	AKUVOX
Model	\$565W
Operating system	LINUX OS
Hardware	RAM: 128 MB ROM: 256 MB
LCD	7" IPS 1280 x 800
Capacity	Contacts: 500 Messages: 100 Call records: 100
Operation mode	Capacitive touch panel
Inputs	8 x configurable alarm, 1 x buzzer and 1 x RS485
Outputs	1 x relay
Audio	Two-way audio with noise-reduced microphone and speaker with Crystal Clear Audio technology
Audio Format	SIP v1 (RFC2543), SIP v2 (RFC3261), G.711a, G.711?, G.729, G.722 DTMF (RFC2833), SIP Info
Remote access	SmartPlus cell phone application or configuration via WEB browser Remote access by Cloud: Included
Mode of operation	Local network and/or via cloud in different networks
Firmware updates	Remote with cloud via installer account or via web browser locally
Network interface	Ethernet 10/100 BaseT / WiFi 802.11b/g/n RTSP / ONVIF
Power	DC 12 V / 600 mA máx. Standard PoE (IEEE802.3af)
Temp. operation	-10 °C ~ +45 °C
Dimensions	278 (W) x 164 (H) x 23 (D) mm
Weight	800 g